

Design: Gothic



Core Area Sq. Feet	Nominal Duct Size in Inches	Core Velocity	100	200	300	400	500	600	700	800	900	1000
		Velocity Pressure	0.001	0.002	0.006	0.01	0.016	0.022	0.031	0.04	0.051	0.062
		TP: Total Pressure	0.003	0.014	0.031	0.056	0.09	0.131	0.175	0.225	0.29	0.355
0.2	10x4 6x6	CFM	19	38	56	75	94	113	132	150	169	188
		NC				17	23	28	32	35	38	42
		4-Way, 45° Fixed			4-6-9	5-8-13	6-9-15	8-11-18	9-13-21	10-14-20	11-16-23	12-17-25
		2-Way, 45° Fixed			5-7-11	6-9-15	8-11-18	9-14-22	10-15-21	12-17-25	13-20-32	15-22-35
		1-Way, Straight			6-9-14	8-11-18	9-14-22	11-15-22	12-18-26	14-21-34	16-24-38	16-26-42
0.26	12x4 8x6	CFM	24	47	75	99	122	146	169	197	221	244
		NC			10	18	24	29	33	36	40	43
		4-Way, 45° Fixed		3-4-7	4-5-6	6-9-14	7-10-16	8-12-20	10-13-19	11-15-22	12-17-25	13-20-32
		2-Way, 45° Fixed		3-5-8	5-6-8	7-9-12	8-12-20	10-14-20	11-16-23	13-19-31	14-21-34	16-24-38
		1-Way, Straight		4-5-6	6-8-11	8-11-15	10-14-20	12-17-24	13-20-32	15-23-37	17-26-41	19-28-45
0.3	14x4	CFM	28	56	85	113	141	169	197	226	254	282
		NC			10	19	24	29	33	37	41	44
		4-Way, 45° Fixed		3-4-7	4-5-6	6-8-10	7-10-13	9-12-17	10-14-20	11-16-23	12-18-26	14-21-33
		2-Way, 45° Fixed		3-5-8	5-7-9	7-10-13	9-12-17	10-14-20	12-17-24	13-20-32	16-24-38/	16-24-39
		1-Way, Straight		4-5-6	6-8-11	8-11-16	10-15-21	12-17-25	14-21-34	16-24-38	18-27-43	20-29-47
0.35	16x4 12x5 10x6 8x8	CFM	33	66	99	132	165	197	230	263	296	329
		NC			11	19	25	30	34	38	41	44
		4-Way, 45° Fixed		3-4-7	5-7-11	6-9-15	8-11-18	9-13-21	10-15-21	12-17-24	13-19-31	14-21-34
		2-Way, 45° Fixed		4-6-9	5-8-13	7-10-13	9-13-21	10-15-21	12-17-25	14-21-33	15-23-37	17-26-41
		1-Way, Straight		4-5-6	7-9-12	9-12-17	10-15-21	12-18-26	15-22-35	17-25-40	18-27-44	20-31-49
0.4	18x4 12x6	CFM	38	75	113	150	188	226	263	301	338	376
		NC			12	20	26	31	35	38	42	45
		4-Way, 45° Fixed		3-5-8	5-6-7	6-8-11	8-11-15	9-13-18	11-15-22	12-17-25	13-20-32	15-22-35
		2-Way, 45° Fixed		4-6-9	6-8-10	8-10-14	9-13-18	11-15-22	12-18-26	14-21-34	16-24-38	18-26-42
		1-Way, Straight		5-6-7	7-9-12	9-13-18	11-15-22	13-19-31	15-22-36	17-26-41	19-29-46	21-32-51
0.45	20x4 14x6 10x8	CFM	42	85	127	169	212	254	296	338	381	423
		NC			12	20	27	31	35	40	43	46
		4-Way, 45° Fixed		3-5-8	5-6-8	6-9-15	8-12-19	10-13-19	11-15-22	12-18-26	14-21-33	15-23-37
		2-Way, 45° Fixed		4-6-9	6-8-10	8-12-19	10-13-19	11-16-23	13-19-31	15-22-35	16-24-39	18-27-44
		1-Way, Straight		5-7-11	7-11-17	9-14-22	11-16-23	13-20-32	15-23-37	18-26-42	20-29-47	22-33-53
0.55	24x4 16x6 12x8	CFM	52	103	155	207	259	310	362	414	465	517
		NC			14	21	27	32	36	41	43	46
		4-Way, 45° Fixed	2-3-4	3-5-8	5-7-12	7-10-16	8-12-20	10-14-20	12-17-24	13-19-31	15-22-35	16-24-39
		2-Way, 45° Fixed	2-3-5	6-6-10	6-9-15	8-12-20	10-14-20	12-17-25	14-21-33	15-23-37	17-26-41	19-29-46
		1-Way, Straight	2-4-6	5-7-12	8-11-18	10-13-19	12-17-25	14-21-34	16-24-39	18-27-44	21-31-50	23-35-56
0.62	18x6 10x10	CFM	56	118	174	235	291	348	409	465	526	583
		NC			14	22	28	33	37	41	44	47
		4-Way, 45° Fixed	2-3-4	4-6-9	5-8-13	7-11-17	9-13-21	10-15-21	12-17-24	13-20-32	15-22-36	17-25-40
		2-Way, 45° Fixed	2-3-5	4-6-10	6-9-15	8-12-20	10-16-25	12-17-25	14-21-34	16-24-38	18-27-43	20-29-47
		1-Way, Straight	2-3-6	5-7-12	8-11-18	10-14-20	12-19-30	15-22-35	17-26-41	19-29-46	21-32-51	24-36-57
0.7	30x4 20x6 14x8 12x10	CFM	66	132	197	263	329	395	461	526	592	658
		NC	0	0	15	22	28	33	37	42	44	47
		4-Way, 45° Fixed	2-3-5	4-6-9	5-8-13	7-11-17	9-13-21	10-15-21	12-17-25	14-21-33	15-23-37	17-26-41
		2-Way, 45° Fixed	2-4-6	5-7-11	7-10-16	9-13-20	10-15-21	12-18-26	15-22-35	17-25-40	18-27-44	20-31-49
		1-Way, Straight	3-4-7	5-8-13	8-12-19	10-15-21	12-19-30	15-22-36	18-26-42	20-29-47	22-33-53	25-37-59
0.81	36x4 24x6 16x8 14x10	CFM	75	150	230	306	381	456	531	611	686	761
		NC			16	23	29	34	38	42	45	48
		4-Way, 45° Fixed	2-3-5	4-6-9	6-9-14	8-11-18	9-14-22	11-15-22	12-18-26	14-21-34	16-24-38	18-27-43
		2-Way, 45° Fixed	2-4-6	5-7-11	7-10-16	9-14-22	11-15-22	13-19-31	15-22-36	17-26-41	19-29-46	21-32-51
		1-Way, Straight	3-4-7	5-8-13	8-12-20	11-15-22	13-20-32	16-24-38	18-27-44	20-31-49	23-34-55	26-39-62
0.87	18x8 12x12	CFM	80	165	244	329	409	489	573	653	738	818
		NC			16	23	29	34	38	42	45	48
		4-Way, 45° Fixed	2-3-5	4-6-9	6-9-14	8-12-19	10-13-19	11-16-23	13-19-31	15-22-35	16-24-39	18-27-43
		2-Way, 45° Fixed	2-4-6	5-7-11	7-11-17	9-14-22	11-16-23	13-20-32	15-23-37	18-26-42	20-39-47	22-32-52
		1-Way, Straight	3-4-7	6-9-14	8-12-20	11-15-22	13-20-32	16-24-39	19-28-45	21-31-50	23-35-56	26-39-63

Core Area Sq. Feet	Nominal Duct Size in Inches	Core Velocity	100	200	300	400	500	600	700	800	900	1000
		Velocity Pressure	0.001	0.002	0.006	0.01	0.016	0.022	0.031	0.04	0.051	0.062
		TP: Total Pressure	0.003	0.014	0.031	0.056	0.09	0.131	0.175	0.225	0.29	0.355
1.02	30x6 20x8 16x10 14x12	CFM	94	193	287	385	479	573	672	766	865	959
		NC			17	24	30	35	40	43	46	49
		4-Way, 45° Fixed	2-3-5	4-6-10	6-9-15	8-12-19	10-14-20	12-17-24	13-20-32	15-22-36	17-26-41	19-28-45
		2-Way, 45° Fixed	2-4-6	5-7-12	7-11-17	10-13-19	12-17-24	14-21-33	16-24-29	18-27-43	20-31-49	23-34-55
		1-Way, Straight	3-4-7	6-9-14	9-13-21	11-17-27	14-21-34	17-25-40	19-29-46	22-32-52	25-37-59	27-41-65
1.15	24x8 18x10 16x12	CFM	108	216	324	432	541	649	757	865	978	1081
		NC			17	25	31	35	40	44	47	50
		4-Way, 45° Fixed	2-3-5	4-6-10	6-9-15	8-12-20	10-15-21	12-17-25	14-21-33	16-24-38	18-26-42	19-29-46
		2-Way, 45° Fixed	2-4-6	5-7-12	8-11-18	10-13-19	12-17-25	14-21-34	17-25-40	19-28-45	21-31-50	23-35-56
		1-Way, Straight	3-5-8	6-9-15	9-14-22	12-17-24	15-22-35	17-26-41	20-29-47	22-34-54	25-37-60	28-42-68
1.25	36x6 20x10 14x14	CFM	118	235	353	470	588	705	823	940	1053	1175
		NC			17	25	31	36	41	44	47	50
		4-Way, 45° Fixed	2-3-5	4-5-6	6-8-11	8-12-20	10-15-21	12-17-25	14-21-34	16-24-38	18-27-43	20-29-47
		2-Way, 45° Fixed	2-4-6	5-6-8	8-10-14	10-14-20	12-18-26	15-22-35	17-26-41	19-29-46	21-32-51	24-26-57
		1-Way, Straight	3-5-8	6-8-11	9-13-18	12-17-25	15-22-35	18-26-42	20-30-48	23-34-55	26-39-62	29-43-69
1.35	16x14 18x12	CFM	127	254	381	508	635	761	888	1015	1147	1269
		NC			18	25	31	36	41	44	47	50
		4-Way, 45° Fixed	2-4-6	4-5-6	7-10-16	9-13-21	10-15-21	12-18-26	15-22-35	16-24-39	18-27-43	20-30-48
		2-Way, 45° Fixed	3-4-7	5-7-9	8-12-19	10-15-21	12-18-26	15-22-36	18-26-42	20-29-47	22-33-53	25-37-59
		1-Way, Straight	3-5-8	6-8-11	10-13-19	12-17-25	15-22-36	18-27-43	21-31-50	23-35-56	26-39-63	29-44-70
1.53	30x8 24x10 20x12 18x14 16x16	CFM	146	287	432	573	719	865	1006	1147	1297	1438
		NC			18	26	32	37	42	45	48	51
		4-Way, 45° Fixed	2-4-6	5-6-7	7-10-16	9-13-21	11-15-22	13-19-31	15-22-36	17-25-40	19-28-45	21-31-50
		2-Way, 45° Fixed	3-4-7	5-7-9	8-12-19	10-15-21	13-20-32	15-23-37	18-27-43	20-30-48	23-34-55	25-37-60
		1-Way, Straight	3-5-8	7-9-12	10-13-19	12-18-26	15-23-37	18-27-44	21-32-51	24-26-58	27-41-65	30-46-73
1.82	36x8 30x10 24x12 20x14 18x16	CFM	171	343	512	686	855	1025	1194	1372	1542	1711
		NC			19	27	33	37	42	46	49	52
		4-Way, 45° Fixed	2-4-6	5-6-7	7-11-17	9-14-22	11-16-23	13-20-32	15-23-37	18-26-42	20-29-47	22-33-53
		2-Way, 45° Fixed	3-4-7	6-8-10	8-12-20	11-16-23	14-21-33	16-24-29	19-28-45	21-31-50	24-36-57	26-39-63
		1-Way, Straight	3-5-8	7-9-12	10-14-20	13-20-32	16-24-39	19-29-46	22-34-54	25-37-60	29-42-68	32-48-76
2.1	24x14 30x16 18x18	CFM	197	395	592	790	987	1184	1382	1579	1777	1974
		NC	0	0	20	27	33	38	43	46	49	52
		4-Way, 45° Fixed	2-4-6	5-6-8	8-11-18	10-13-19	12-17-24	14-21-34	16-24-39	18-27-44	20-31-49	23-34-55
		2-Way, 45° Fixed	3-4-7	6-8-10	9-13-21	12-17-24	14-21-34	17-25-40	19-29-46	22-32-52	25-37-59	28-41-66
		1-Way, Straight	4-6-9	7-10-13	10-15-21	14-21-33	17-25-40	20-30-48	23-34-55	26-39-62	29-44-70	33-50-80
2.35	36x10 30x12 24x16 20x18	CFM	221	442	663	884	1109	1325	1542	1767	1993	2209
		NC			20	28	34	38	43	47	50	53
		4-Way, 45° Fixed	2-4-6	5-6-8	8-11-18	10-14-20	12-17-25	15-22-35	17-25-40	19-28-45	21-31-50	24-36-57
		2-Way, 45° Fixed	3-5-8	6-8-11	9-14-22	12-17-24	15-22-35	18-26-42	20-30-48	22-34-54	25-38-61	28-42-68
		1-Way, Straight	4-6-9	7-10-13	11-15-22	14-21-33	18-26-42	20-31-49	24-36-57	27-40-64	30-45-72	34-51-82
2.68	36x12 30x14 24x18 20x20	CFM	254	503	757	1006	1260	1513	1767	2012	2265	2519
		NC			21	28	34	40	44	47	50	53
		4-Way, 45° Fixed	3-4-7	5-7-9	8-12-19	10-15-21	12-18-26	15-22-36	18-26-42	20-29-47	22-32-52	25-37-59
		2-Way, 45° Fixed	3-5-8	6-8-11	9-14-22	12-17-25	15-22-36	20-30-48	20-31-49	23-35-56	26-39-62	29-44-70
		1-Way, Straight	4-6-9	8-10-14	11-16-23	15-22-35	18-27-43	21-32-51	25-37-59	28-41-66	31-47-75	35-53-85
3.15	36x16 30x18 24x24	CFM	296	592	888	1184	1485	1777	2068	2369	2670	2961
		NC		10	21	29	35	41	45	48	51	54
		4-Way, 45° Fixed	3-4-7	5-7-9	8-12-19	11-15-22	13-19-31	15-23-37	18-27-43	20-31-49	23-34-55	26-39-62
		2-Way, 45° Fixed	3-5-8	7-9-12	10-14-20	12-18-26	16-24-38	19-28-45	21-32-51	24-36-58	27-41-65	30-46-73
		1-Way, Straight	4-5-6	8-11-15	12-17-24	15-22-36	19-28-45	22-3-53	26-39-62	29-43-69	33-49-79	37-56-89
3.65	36x18 30x20	CFM	343	686	1034	1372	1711	2059	2406	2745	3083	3431
		NC		11	22	30	36	41	45	49	52	55
		4-Way, 45° Fixed	3-4-7	5-7-9	8-12-19	11-15-22	13-19-31	15-23-37	18-27-43	21-31-50	24-36-57	27-40-64
		2-Way, 45° Fixed	3-5-8	7-9-12	10-14-20	12-18-26	16-24-38	19-28-45	21-32-51	25-37-60	28-42-68	32-48-76
		1-Way, Straight	4-5-6	8-11-15	12-17-24	15-22-36	19-28-45	22-33-53	26-39-62	30-45-72	34-51-83	38-57-92

CFM: Cubic Feet per Minute

*All pressures are in inches of water.

Page #2 of 2

FPM: Feet per Minute

* Blank areas denote NC values less than 10 and CFM values less than 50.

TP: Total Pressure, inches w.g.

*Throw values are measured in feet for terminal velocities of 150/100/50 FPM.

T: Throw in feet

*Throw values are based on fixed louvers set at 45 degrees.

NC: Noise Criteria

* Throw may be increased or decreased by as much as 20% by changing angle of louver.